



# Rubber Sheet Roll

## TECHNICAL DATA SHEET

**CLOTH INSERTED NEOPRENE RUBBER**

**COTTON PLY PER 1/16" THICKNESS**

**SOLID RUBBER, SYNTHETIC MATERIAL.**



### CLOTH INSERTED NEOPRENE RUBBER - Technical Specification Data

**CLOTH INSERTED NEOPRENE RUBBER** is a rubber that uses a cotton, one ply insert ideal for stress applications such as gasketing and diaphragms. Fabric inserted Neoprene rubber is well suited for applications requiring an extreme amount of tear strength, resilient rubber for outdoor and mechanical environments.

Fabric insert rubber is also used for conveyor belting and trailer / truck mud flaps.

<b>COLOR:</b>	BLACK
<b>SURFACE:</b>	SMOOTH
<b>TEMPERATURE RANGE:</b>	- 30° F TO 220° F
<b>TENSILE:</b>	1500 PSI
<b>DUROMETER:</b>	70A NOMINAL
<b>ELONGATION:</b>	175%

ADHESIVE DATA	
<b>THICKNESS</b>	5 MILS
<b>SURFACE</b>	RELEASE LINER ONE SIDE
<b>TEMPERATURE</b>	250° F
<b>COMPOSITION</b>	ACRYLIC
<b>FDA</b>	NO

### RUBBER SHEET ROLL

PO BOX 171  
Shippensburg, PA 17257  
Phone: 866.834.8606  
Fax: 888.440.5797  
E-mail: info@rubbersheetroll.com



[www.facebook.com/Rubber-Sheet-Roll](http://www.facebook.com/Rubber-Sheet-Roll)

[www.twitter.com/rubbersheetroll](http://www.twitter.com/rubbersheetroll)



**Fire Rated:** Not Fire Rated | **Chemical Resistance:** Moderate  
**UV Rated:** Good | **Composition:** Synthetic Rubber

