



Rubber Sheet Roll

TECHNICAL DATA SHEET

EPDM RUBBER, CLOTH INSERTED

EXCELLENT OZONE & CLOTH / FABRIC INSERT

SOLID RUBBER, SYNTHETIC MATERIAL.



EPDM CLOTH INSERTED RUBBER - Technical Specification Data

EPDM - EPDM Cloth Inserted Rubber is made up of EPDM rubber with a fiber-glass cloth insert added incrementally throughout the thickness of the material. This process gives the rubber added durability and a higher degree of strength under hot or cold loads. Fabric reinforced EPDM is primarily used in gasketing applications as a high strength diaphragm between high pressure or low pressure junctions.

COLOR:	BLACK
SURFACE:	SMOOTH
TEMPERATURE RANGE:	- 40° F TO 245° F
TENSILE:	1500 PSI
DUROMETER:	70 A NOMINAL
ELONGATION:	100 %

ADHESIVE DATA IF APPLIED TO THE ABOVE MATERIAL	
THICKNESS	5 MILS
SURFACE	RELEASE LINER ONE SIDE
TEMPERATURE	250° F
COMPOSITION	ACRYLIC
FDA	NO

Fire Rated: Not Fire Rated | **Chemical Resistance:** Excellent

UV Rated: Excellent | **Composition:** Synthetic Rubber

RUBBER SHEET ROLL

PO BOX 171
Shippensburg, PA 17257
Phone: 866.832.6006
Fax: 888.440.5797
E-mail: info@rubbersheetroll.com



www.facebook.com/Rubber-Sheet-Roll

www.twitter.com/rubbersheetroll

