



Rubber Sheet Roll

TECHNICAL DATA SHEET

EPDM RUBBER ROLL

Has excellent resistance to phosphate ester fluids, brake fluids (glycol base), steam, weather, and ozone.



EPDM RUBBER - Technical Specification Data

EPDM RUBBER rolls are available for a range of applications in the industrial and residential markets. This type of EPDM rubber has excellent stretching capabilities while remaining strong enough to be elastic. With an average elongation of 200% and an average of 1,000 PSI tensile strength, EPDM rubber rolls will handle most tough industrial environments and moderate to heavy alkaline and chemical resistive situations.

COLOR:	BLACK
SURFACE:	SMOOTH
TEMPERATURE RANGE:	- 40° F TO 280° F
TENSILE:	800 PSI
DUROMETER:	50A NOMINAL
ELONGATION:	200 %

ADHESIVE DATA	
THICKNESS	5 MILS
SURFACE	RELEASE LINER ONE SIDE
TEMPERATURE	250° F
COMPOSITION	ACRYLIC
FDA	NO

RUBBER SHEET ROLL

PO BOX 171
Shippensburg, PA 17257
Phone: 866.834.8606
Fax: 888.440.5797
E-mail: info@rubbersheetroll.com



www.facebook.com/Rubber-Sheet-Roll

www.twitter.com/rubbersheetroll



Fire Rated: Not Fire Rated |

Chemical Resistance: GOOD

UV Rated: EXCELLENT |

Composition: Synthetic Blend