



Rubber Sheet Roll

TECHNICAL DATA SHEET



HIGH STRENGTH EPDM RUBBER

HIGH TENSILE STRENGTH

SOLID RUBBER, UV RESISTANT

HIGH STRENGTH EPDM RUBBER - Technical Specification Data

HIGH STRENGTH EPDM RUBBER High Strength EPDM Rubber is a perfect material for outdoor or mechanical applications. Because of its impressive strength, this EPDM grade of rubber holds up to the rigors of oilfields, power generation plants, hydro-electric equipment and rubber pads for shock absorption. The EPDM High Strength is not affected by sunlight, UV rays or exposure to solar panel reflections.

COLOR:	BLACK
SURFACE:	SMOOTH
TEMPERATURE RANGE:	- 60° F TO 245° F
TENSILE:	1200 PSI
DUROMETER:	60A NOMINAL
ELONGATION:	190%

ADHESIVE DATA	
THICKNESS	5 MILS
SURFACE	RELEASE LINER ONE SIDE
TEMPERATURE	250° F
COMPOSITION	ACRYLIC
FDA	NO

RUBBER SHEET ROLL

PO BOX 171
Shippensburg, PA 17257
Phone: 866.834.8606
Fax: 888.440.5797
E-mail: info@rubbersheetroll.com



www.facebook.com/Rubber-Sheet-Roll

www.twitter.com/rubbersheetroll



Fire Rated: Not Fire Rated | **Chemical Resistance : Good**

UV Rated: Excellent | **Composition: Synthetic Rubber**