



Rubber Sheet Roll

TECHNICAL DATA SHEET

NEOPRENE RUBBER

ALSO KNOWN AS COMMERCIAL GRADE NEO

SOLID RUBBER, SYNTHETIC MATERIAL.



NEOPRENE RUBBER - Technical Specification Data

NEOPRENE RUBBER, COMMERCIAL GRADE is a very common grade of chloroprene material used industry wide for many applications. Com Grade Neo with stands most detergents, mild petroleum and can withstand moderate ozone exposure for a limited amount of time. Neoprene rubber is well suited for applications requiring a stable, resilient rubber for mostly indoor and sheltered environments. Commercial Grade Neo can also be used as a gasket material.

COLOR:	BLACK
SURFACE:	SMOOTH
TEMPERATURE RANGE:	- 20° F TO 212° F
TENSILE:	975 PSI
DUROMETER:	60A NOMINAL
ELONGATION:	275 %

ADHESIVE DATA	
THICKNESS	5 MILS
SURFACE	RELEASE LINER ONE SIDE
TEMPERATURE	250° F
COMPOSITION	ACRYLIC
FDA	NO

RUBBER SHEET ROLL

PO BOX 171
Shippensburg, PA 17257
Phone: 866.834.8606
Fax: 888.440.5797
E-mail: info@rubbersheetroll.com



www.facebook.com/Rubber-Sheet-Roll

www.twitter.com/rubbersheetroll



Fire Rated: Not Fire Rated | Chemical Resistance: Moderate
UV Rated: Moderate | Composition: Synthetic Rubber