



Rubber Sheet Roll

TECHNICAL DATA SHEET

ZZR 765 SILICONE RUBBER

TOTALLY SYNTHETIC, HIGHER TEMPERATURE

SOLID RUBBER, SYNTHETIC MATERIAL.



ZZR 765 SILICONE RUBBER - Technical Specification Data

ZZR 765 SILICONE RUBBER has several designations ... ZZR765, or ZZ-R-765b or ZZ-R-765e. The ZZR765 military specification is now listed within A-A-59588. This particular ZZR 765 rubber call out is Class 2A & 2B grade 50. A full Military specification is included in the following pages of this document.

COLOR:	ORANGE, RED OR BLACK
SURFACE:	SMOOTH
TEMPERATURE RANGE NOMINAL:	- 60° F TO 490° F
TENSILE:	750 PSI
DUROMETER:	50A NOMINAL
ELONGATION NOMINAL:	300 %

Fire Rated: Not Fire Rated | **Chemical Resistance:** EXCELLENT

ADHESIVE DATA	
THICKNESS	5 MILS
SURFACE	RELEASE LINER ONE SIDE
TEMPERATURE	300° F
COMPOSITION	SILICONE
FDA	NO

UV Rated: VERY GOOD | **Composition:** Synthetic / INERT

RUBBER SHEET ROLL

PO BOX 171
Shippensburg, PA 17257
Phone: 866.834.8606
Fax: 888.440.5797
E-mail: info@rubbersheetroll.com



www.facebook.com/Rubber-Sheet-Roll

www.twitter.com/rubbersheetroll

